



ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	5W
MAX.SWITCHING CURRENT	DC 0.4A / AC 0.28A
MAX.SWITCHING VOLTAGE	125VAC 175VDC

		10				11	
DESIGN DATA							
CODE		N/A					
UNIT		mm					
KIND OF FLUID		-					
PRESS.	DESIGN	Max. 10		Kg/Cm ²			
	OPERATING	-		Kg/Cm ²			
TEMP. (SENSOR)	DESIGN	-20 ~ 80		°C			
	OPERATING	-		°C			
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60		°C			
	OPERATING	-		°C			
SP.GR.		MORE THAN 0.74					
VISCOSITY		10 P / 1 Pa.s					
ENCLOSURE		WEATHER PROOF					
FLANGE SIZE		JIS 10K 80A FF					
FLOAT TYPE		ø49x50L					
TAG NO.		L	L1	L2	L3	L4	
<div>NOTES</div> <div>1. () Dimensions are reference dimensions.</div>							
<div>REVISION</div>							
7	COUPLING	316SS	1				
6	FLOAT	316SS	1				
5	FLOAT STOPPER	304SS	2				
4	STEM	304SS	1	ø13.8			
3	FLANGE	304SS	1				
2	HOUSING	ADC12	1				
1	COVER	ADC12	1				
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK		
BILL OF MATERIAL							
CUSTOMER							
PROJECT							
TITLE							
FLOAT TYPE LEVEL SWITCH							
ST-1S-A-1-A-1-D-1-B-3							
ASSEMBLY DRAWING							
MANUFACTURER							
SeoJin Instech Co., Ltd.							
SCALE		ERP CODE	-	Work Order No.	-	REV.	
N/S	DWG NO.	SJ-M003-DWG-AP004					
9		10		11			