



ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	50W / 70VA
MAX.SWITCHING CURRENT	0.5A
MAX.SWITCHING VOITAGE	350VDC 300VAC

DESIGN DATA					
CODE	N/A				
UNIT	mm				
KIND OF FLUID	—				
PRESS.	DESIGN	Max. 10		Kg/Cm ²	
	OPERATING	—		Kg/Cm ²	
TEMP. (SENSOR)	DESIGN	-20 ~ 80		°C	
	OPERATING	—		°C	
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60		°C	
	OPERATING	—		°C	
SP.GR.		MORE THAN 0.74			
VISCOSITY		10 P / 1 Pa.s			
ENCLOSURE		WEATHER PROOF			
FLANGE SIZE		JIS 10K 80A FF			
FLOAT TYPE		ø49x50L			
TAG NO.	L	L1	L2	L3	L4

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	COUPLING	316SS	1		
6	FLOAT	316SS	3		
5	FLOAT STOPPER	304SS	6		
4	STEM	304SS	1	ø13.8	
3	FLANGE	304SS	1		
2	HOUSING	ADC12	1		
1	COVER	ADC12	1		

NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK
----	-------------	----------	------	---------------	--------

BILL OF MATERIAL					
CUSTOMER		-			
PROJECT		-			
TITLE		FLOAT TYPE LEVEL SWITCH ST-4S-D-2-A-1-D-1-B-3 ASSEMBLY DRAWING			
MANUFACTURER		SeoJin Instech Co.,Ltd.			
SCALE	DWG NO.	ERP CODE	Work Order No.	REV.	
N/S	SJ-M003-DWG-AP028	-	-		