


| ELECTRIC RATING (RESISTIVE) | |
|-----------------------------|---------------|
| MAX.CONTACT RATING | 50W / 70VA |
| MAX.SWITCHING CURRENT | 0.5A |
| MAX.SWITCHING VOITAGE | 350VDC 300VAC |



WIRING DIAGRAM

| DESIGN DATA | | | |
|---------------------|----------------|----------|--------------------|
| CODE | N/A | | |
| UNIT | mm | | |
| KIND OF FLUID | - | | |
| PRESS. | DESIGN | Max. 5 | Kg/Cm ² |
| | OPERATING | AMT | Kg/Cm ² |
| TEMP. (SENSOR) | DESIGN | -20 ~ 60 | °C |
| | OPERATING | AMB | °C |
| TEMP. (ELECTRONICS) | DESIGN | -20 ~ 60 | °C |
| | OPERATING | AMB | °C |
| SP.GR. | MORE THAN 0.62 | | |
| VISCOSITY | 10 P / 1 Pa.s | | |
| ENCLOSURE | WEATHER PROOF | | |
| FLANGE SIZE | JIS 10K 80A FF | | |
| FLOAT TYPE | ø75x80L | | |

NOTES

1. () Dimensions are reference dimensions.

REVISION

| | | | | | |
|---|---------------|-----------|---|-----|--|
| 6 | FLOAT | PVC | 4 | | |
| 5 | FLOAT STOPPER | PVC | 8 | | |
| 4 | STEM | 304SS+PVC | 1 | ø22 | |
| 3 | FLANGE | PVC | 1 | | |
| 2 | HOUSING | ADC12 | 1 | | |
| 1 | COVER | ADC12 | 1 | | |

| NO | DESCRIPTION | MATERIAL | Q'TY | SPECIFICATION | REMARK |
|----|-------------|----------|------|---------------|--------|
|----|-------------|----------|------|---------------|--------|

BILL OF MATERIAL

| | |
|----------|---|
| CUSTOMER | - |
|----------|---|

| | |
|---------|---|
| PROJECT | - |
|---------|---|

| | |
|-------|--|
| TITLE | FLOAT TYPE LEVEL SWITCH ST-4S-D-1-C-1-A-1-B-3 ASSEMBLY DRAWING |
|-------|--|

| | |
|--------------|--------------------------|
| MANUFACTURER | SeoJin Instech Co., Ltd. |
|--------------|--------------------------|

| | | | | | | | |
|---------|-------------------|----------|---|----------------|---|------|--|
| SCALE | N/S | ERP CODE | - | Work Order No. | - | REV. | |
| DWG NO. | SJ-M003-DWG-AP023 | | | | | | |