



ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	5W
MAX.SWITCHING CURRENT	DC 0.4A / AC 0.28A
MAX.SWITCHING VOITAGE	125VAC 175VDC

DESIGN DATA									
CODE		N/A							
UNIT		mm							
KIND OF FLUID		—							
PRESS.	DESIGN	Max. 10			Kg/Cm ²				
	OPERATING	—			Kg/Cm ²				
TEMP. (SENSOR)	DESIGN	-20 ~ 80			°C				
	OPERATING	—			°C				
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60			°C				
	OPERATING	—			°C				
SP.GR.		MORE THAN 0.74							
VISCOSITY		10 P / 1 Pa.s							
ENCLOSURE		WEATHER PROOF							
FLANGE SIZE		JIS 10K 80A FF							
FLOAT TYPE		ø49x50L							
TAG NO.		L	L1	L2	L3	L4			
<div>NOTES</div> <div>1. () Dimensions are reference dimensions.</div>									
<div>REVISION</div>									
7	COUPLING	316SS	1						
6	FLOAT	316SS	3						
5	FLOAT STOPPER	304SS	6						
4	STEM	304SS	1		ø13.8				
3	FLANGE	304SS	1						
2	HOUSING	ADC12	1						
1	COVER	ADC12	1						
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK				
BILL OF MATERIAL									
CUSTOMER —									
PROJECT —									
TITLE FLOAT TYPE LEVEL SWITCH ST-3S-C-1-A-1-D-1-B-3 ASSEMBLY DRAWING									
MANUFACTURER <div> SeoJin Instech Co., Ltd.</div>									
SCALE		ERP CODE	Work Order No.		REV.				
N/S	DWG NO.	SJ-M003-DWG-AP016		