


ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	5W
MAX.SWITCHING CURRENT	DC 0.4A / AC 0.28A
MAX.SWITCHING VOLTAGE	125VAC 175VDC

		10				11	
DESIGN DATA							
CODE		N/A					
UNIT		mm					
KIND OF FLUID			-				
PRESS.	DESIGN	Max. 10			Kg/Cm <sup>2</sup>		
	OPERATING	-			Kg/Cm <sup>2</sup>		
TEMP. (SENSOR)	DESIGN	-20 ~ 80			°C		
	OPERATING	-			°C		
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60			°C		
	OPERATING	-			°C		
SP.GR.			MORE THAN 0.74				
VISCOSITY			10 P / 1 Pa.s				
ENCLOSURE			WEATHER PROOF				
FLANGE SIZE			JIS 10K 80A FF				
FLOAT TYPE			ø49x50L				
TAG NO.		L	L1	L2	L3	L4	
NOTES							
1. ( ) Dimensions are reference dimensions.							
REVISION							
7	COUPLING		316SS	1			
6	FLOAT		316SS	3			
5	FLOAT STOPPER		304SS	6			
4	STEM		304SS	1	ø13.8		
3	FLANGE		304SS	1			
2	HOUSING		ADC12	1			
1	COVER		ADC12	1			
NO	DESCRIPTION		MATERIAL	Q'TY	SPECIFICATION	REMARK	
BILL OF MATERIAL							
CUSTOMER							
PROJECT							
TITLE							
FLOAT TYPE LEVEL SWITCH							
ST-4S-D-1-A-1-D-1-B-3							
ASSEMBLY DRAWING							
MANUFACTURER							
SeoJin Instech Co., Ltd.							
SCALE			ERP CODE	Work Order No.		REV.	
N/S	DWG NO.		SJ-M003-DWG-AP022				