



ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	50W / 70VA
MAX.SWITCHING CURRENT	0.5A
MAX.SWITCHING VOITAGE	350VDC 300VAC

DESIGN DATA					
CODE	N/A				
UNIT	mm				
KIND OF FLUID	-				
PRESS.	DESIGN	Max. 1		Kg/Cm ²	
	OPERATING	-		Kg/Cm ²	
TEMP. (SENSOR)	DESIGN	-20 ~ 80		°C	
	OPERATING	-		°C	
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60		°C	
	OPERATING	-		°C	
SP.GR.		MORE THAN 1.0			
VISCOSITY		10 P / 1 Pa.s			
ENCLOSURE		WEATHER PROOF			
FLANGE SIZE		JIS 10K 80A FF			
FLOAT TYPE		ø66x79L			
TAG NO.	L	L1	L2	L3	L4

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	COUPLING	316SS	1		
6	FLOAT	PTFE	4		
5	FLOAT STOPPER	PTFE	8		
4	STEM	304SS+PTFE	1	φ16	
3	FLANGE	304SS+PTFE	1		
2	HOUSING	ADC12	1		
1	COVER	ADC12	1		

NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK
BILL OF MATERIAL					
CUSTOMER					
PROJECT					
TITLE					
FLOAT TYPE LEVEL TRANSMITTER ST-4S-D-2-D-1-D-1-B-3 ASSEMBLY DRAWING					
MANUFACTURER					
SeoJin Instech Co., Ltd.					
SCALE	DWG NO.	ERP CODE	Work Order No.	REV.	
N/S					
SJ-M003-DWG-AP030					