



COMPONENT ARRANGEMENT



DESIGN DATA

CODE	N/A		
UNIT	mm		
KIND OF FLUID	—		
PRESS.	DESIGN	20 (Max.)	Kg/Cm ²
	OPERATING	—	Kg/Cm ²
TEMP. (SENSOR)	DESIGN	-10 ~ 150°C (180°C OPTION)	
	OPERATING	— °C	
TEMP. (ELECTRONICS)	DESIGN	-10 ~ 60 °C	
	OPERATING	— °C	
POWER SUPPLY	100~120/200 to 240AC 50/60Hz or 24V DC (OPTION)		
ENCLOSURE	<input type="checkbox"/> WEATHER PROOF		
	<input type="checkbox"/> EXPLOSION PROOF (Ex d IIC T6,IP65)		
RELAY OUTPUT	1SPDT,250V 3A AC,30V 3A DC(RESISTIVE) C-NO : NORMALLY OPEN CONTACT C-NC : NORMALLY CLOSED CONTACT		
DETECTION TIME DELAY	APPROX. 3 to 5 SECONDS FOR COVERED APPROX. 3 to 5 SECONDS FOR FREE		
SENSITIVITY	BULK DENSITY OF 0.2g/cm ² (Min)		
L	1000 mm		
MOUNTING SIZE	JIS 10K 80A FF		
TAG NO.			

NOTES

- INITIAL RESET TIME : APPROX. 15 SEC.
- L (REF. LENGTH = 330~4000)

REVISION

5	EXTENSION PIPE	304SS	1		
4	FLANGE	304SS	1		
3	DETECTION PIPE	304SS	1		
2	COVER	ADC 12	1		
1	HOUSING	ADC 12	1		
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—				
PROJECT	—				
TITLE	VIBRATION TYPE LEVEL SWITCH SVL-25-OP-1-C-1-A-1 ASSEMBLY DRAWING				
MANUFACTURER	SeoJin Instech Co., Ltd.				
SCALE	N/S	ERP CODE	0000	Work Order No.	—
DWG NO.	SJ-M022-DWG-AP004				

△					
△					
△					
△					
△	FOR APPROVAL				
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED