



DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF FLUID	—		
PRESS.	DESIGN	20 (Max.)	Kg/Cm
	OPERATING	—	Kg/Cm
TEMP. (SENSOR)	DESIGN	-10 ~ 150°C (180°C OPTION)	
	OPERATING	—	
TEMP. (ELECTRONICS)	DESIGN	-10 ~ 60	
	OPERATING	—	
POWER SUPPLY		100~120/200 to 240AC 50/60Hz or 24V DC (OPTION)	
ENCLOSURE		<input type="checkbox"/> WEATHER PROOF	
		<input type="checkbox"/> EXPLOSION PROOF (Ex d IIC T6,IP65)	
RELAY OUTPUT		1SPDT,250V 3A AC,30V 3A DC(RESISTIVE) C-NO : NORMALLY OPEN CONTACT C-NC : NORMALLY CLOSED CONTACT	
DETECTION TIME DELAY		APPROX. 3 to 5 SECONDS FOR COVERED APPROX. 3 to 5 SECONDS FOR FREE	
SENSITIVITY		BULK DENSITY OF 0.2g/cm2 (Min)	
L	<input type="checkbox"/> 250 mm(STD)		
	<input type="checkbox"/> OPTION (mm) Max. 1000mm		
MOUNTING SIZE		PT 1"	
TAG NO.			

NOTES

1. INITIAL RESET TIME : APPROX. 15 SEC.

REVISION

4	MOUNTING NIPPLE	304SS	1		
3	DETECTION PIPE	304SS	1		
2	COVER	ADC 12	1		
1	HOUSING	ADC 12	1		
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-				
PROJECT	-				
TITLE	VIBRATION TYPE LEVEL SWITCH SVL-15-A-1-A-1-A-1 ASSEMBLY DRAWING				
MANUFACTURER	SeoJin Instech Co., Ltd.				

△					
△					
△					
△					
△	FOR APPROVAL				
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED

SCALE	N/S	ERP CODE	0000	Work Order No.	-	REV.	
DWG NO.	SJ-M022-DWG-AP001						