



WIRING DIAGRAM

DESIGN DATA

CODE	N/A
UNIT	mm
KIND OF FLUID	-
PRESS.	DESIGN 1(Max.) kg/Cm ² OPERATING - kg/Cm ²
TEMP. (SENSOR)	DESIGN -10 ~ 90 °C OPERATING - °C
TEMP. (ELECTRONICS)	DESIGN -10 ~ 60 °C OPERATING - °C
CONTACT RATING	250V AC 5A
POWER SUPPLY	15-32V DC(2 WIRE)
ENCLOSURE	WEATHER PROOF
OUTPUT	TRANSMITTER 4-20 mA SWITCH □ 2point □ 4point
VISCOSITY	1Pa.s/10P Less
MOISTURE	Max 80%RH

MEASURING RANGE (mm) Max. 20000mm

TAG NO. -

NOTES

REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
7	UNION	304SS	1	1 1/2"	
6	TRANSMITTER ASS'Y	ADC 12	1		
5	DRAIN VALVE	MSBR2	1		
4	HOST GEAR ASS'Y	AC2B	1		
3	SCALE COVER	ADC 12	1		
2	BACK COVER	ADC 12	1		
1	INDICATOR BODY	ADC 12	1		

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-

TITLE	LIQUID TANK LEVEL GAUGE SLT-4400-B(C)-1-A(B)-1-A-1-A ASSEMBLY DRAWING
-------	---

MANUFACTURER

Seojin Instech Co., Ltd.

SCALE

1/2" = 1"

0000

Max. Order No. -

REV.

W/S

SU-MQ21-DWG-AP007

DATE

DESIGNED

REVIEWED

APPROVED