



DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF FLUID	—		
PRESS.	DESIGN	5(Max.)	Kg/Cm ²
	OPERATING	—	Kg/Cm ²
TEMP. (SENSOR)	DESIGN	—10 ~ 120	°C
	OPERATING	—	°C
TEMP. (ELECTRONICS)	DESIGN	—10 ~ 120	°C
	OPERATING	—	°C
CONTACT RATING	250V AC, 0.5A		
POWER SUPPLY	—		
ENCLOSURE	WEATHER PROOF		
SP.GR	0.65(Min.)		
OUTPUT	<input type="checkbox"/> 1 SPST	<input type="checkbox"/>	
	<input type="checkbox"/> 1 SPDT	<input type="checkbox"/>	
VISCOSITY	1Pa.s/10P Less		
MOISTURE	Max 80%RH		
TAG NO.	—		

NOTES

8	COVER	ADC 12	1		
7	HOUSING	ADC 12	1		
6	FLANGE	304SS	1		
5	STEM	304SS	1		
4	SUPPORT	304SS	1		
3	PIN	304SS	1		
2	SHAFT	304SS	1		
1	FLOAT	304SS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

CUSTOMER	—		
PROJECT	—		
TITLE	Magnetic Float Type Level Switch SFM-11-A-1-A-1-A-1 APPROVAL DRAWING		
MANUFACTURER	 SeoJin Instech Co., Ltd.		
SCALE		EBP CODE 0000	Work Order No. —
N/S	DWG NO. SJ-M010-DWG-AP001		
	