


WIRING DIAGRAM



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID		
PRESS.	DESIGN	5(Max.) kg/cm ²
	OPERATING	- kg/cm ²
TEMP.	DESIGN	-10 ~ 120 °C
	OPERATING	- °C
TEMP.	DESIGN	-10 ~ 120 °C
	OPERATING	- °C
(ELECTRONICS)		
CONTACT RATING		250V AC, 0.5A
POWER SUPPLY		-
ENCLOSURE		
SP.GR		WEATHER PROOF
OUTPUT		0.65(Min.)
	<input type="checkbox"/> 1 SPST	<input type="checkbox"/>
	<input type="checkbox"/> 1 SPDT	<input type="checkbox"/>
VISCOSITY		1Pa.s/10P Less
MOISTURE		Max 80%RH

TAG NO.

-

NOTES

REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
8	COVER	ADC 12	1		
7	HOUSING	ADC 12	1		
6	COUPLING	304SS	1		
5	STEM	304SS	1		
4	SUPPORT	304SS	1		
3	PIN	304SS	1		
2	SHAFT	304SS	1		
1	FLOAT	304SS	1		

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-

TITLE	Magnetic Float Type Level Switch SFM-13-A-1-A-1-A-1 APPROVAL DRAWING
-------	--

MANUFACTURER	Seojin Instech Co., Ltd.
SCALE	1:1
DATE	0000
REV	N/S
FOR APPROVAL	
DESCRIPTION	
DATE	
DESIGNED	
REVIEWED	
APPROVED	